

## Screw-type parallel compressor unit low temperature type parameter

Mode	Condensing Temp	To Evaporating temp			Compressor Power (kw)	Liquid receiver (L)	Suction pipe Omm	Supply pipe (mm)	Dimension (LxWxH)	Operating weight (kg)
		23℃	30℃	-40℃						
BFLD60-2	35	175.4	131.8	82.4	90	150	133	42	2875x1325x1620	2080
	45	163.4	122	74.8						
FLD60-3	35	263.1	197.7	123.6	135	200	2x108	54	3538x1325x1785	2600
	45	245.1	183	112.2						
BFLD60-4	35	350.8	263.6	164.8	180	250	2x108	54	4500x1325x1900	3030
	45	326.8	244	149.6						
BFLD60-5	35	438.5	329.5	206	225	300	3x108	54	5300x1572x1900	3485
	45	408.5	305	187						
BFLD60-6	35	526.2	395.4	247.2	270	400	3x133	54	6200x1572x1918	3980
	45	490.2	366	224.4						
BFLD70-2	35	196.6	149.2	95.2	105	150	133	42	2875x1495x1620	2130
	45	184.8	139.2	87						
BFLD70-3	35	294.9	223.8	142.8	157.5	250	2x108	54	4033x1321x1768	2780
	45	277.2	208.8	130.5						
BFLD70-4	35	393.2	298.4	190.4	210	300	2x133	54	4500x1572x1900	3030
	45	369.6	278.4	174						
BFLD70-5	35	491.5	373	238	262.5	400	3x108	54	5300x1572x1900	3220
	45	462	348	217.5						
BFLD70-6	35	589.8	447.6	285.6	315	500	3x133	54	6200x1572x1918	3670
	45	554.4	417.6	261						
BFLD75-2	35	212.4	161.6	103.6	112.5	150	133	42	2875x1495x1620	2160
	45	199.2	150.6	94.8						
BFLD75-3	35	318.06	242.4	155.4	168.75	250	2x108	50	4033x1321x1768	2820
	45	298.8	225.9	142.2						
BFLD75-4	35	424.8	323.2	207.2	225	300	2x133	54	4500x1572x1900	3080
	45	398.4	301.2	189.6						
BFLD75-5	35	531	404	259	281.25	400	3x133	76	5300x1572x1900	3330
	45	498	376.5	237						
BFLD75-6	35	637.2	484.8	310.8	337.5	500	3x133	76	6353x1572x1918	3750
	45	597.6	451.8	284.4						
BFLD125-2	35	358.6	274	177.8	187.5	250	159	54	3380x1520x2270	2550
	45	336.8	255	161.6						
BFLD125-3	35	537.9	411	266.7	281.25	400	2x159	54	4929x1299x2101	3400
	45	505.2	382.5	242.4						
BFLD125-4	35	717.2	548	355.6	375	500	2x159	76	4850x1970x2320	4620
	45	673.6	510	323.2						
BFLD125-5	35	896.5	685	444.5	468.75	600	3x159	76	5500x1970x2420	5450
	45	842	637.5	404						
BFLD125-6	35	1075.8	822	533.4	562.5	800	3x159	76	6400x1970x2420	6150
	45	1010.4	765	484.8						

Screw-type parallel compressor unit high temperature type parameter

Mode	Condensing Temp	To Evaporating temp			Compressor power (kw)	Liquid receiver (L)	Suction pipe (mm)	Supply pipe (mm)	Dimension (L×W×H)	Operating weight (kg)
		+7℃	0℃	-10℃						
BFLZ60-2	35	361.4	2848	195.8	90	150	108	42	2900x1285x1700	1830
	45	325.2	254	170						
BFLZ60-3	35	542.1	427.2	293.7	135	200	2×89	54	3400×1285×1766	2430
	45	487.8	381	255						
BFLZ60-4	35	722.8	569.6	391.6	180	250	2×108	54	4280x1490x1766	2650
	45	650.4	508	340						
BFLZ90-2	35	560	442	304	135	200	133	54	2715x1490x1766	2850
	45	504	394.4	264.4						
BFLZ90-3	35	840	663	456	202.5	300	2x108	76	3900×1490×1766	3650
	45	756	591.6	396.6						
BFLZ90-4	35	1120	884	608	270	400	2×133	76	4700x1490X2015	4510
	45	1008	788.8	528.8						
BFLZ125-2	35	806	630	428	187.5	250	133	57	3800×1700×2100	3220
	45	716	554	365.2						
BFLZ125-3	35	1209	945	642	281.25	400	2×133	76	4600x1700X2100	4320
	45	1074	831	547.8						
BFLZ125-4	35	1612	1260	856	375	500	2x133	76	5600x1700×2100	5310
	45	1432	1108	730.4						
BFLZ140-2	35	918	724	498	210	300	159	76	3800×1850×2100	3280
	45	826	646	432						
BFLZ140-3	35	1377	1086	747	315	400	2x133	76	4600×1850×2100	4430
	45	1239	969	648						
BFLZ140-4	35	1836	1448	996	420	600	2×159	89	5600x1850X2100	5520
	45	1652	1292	864						